



BEHR PRO® Pre-Catalyzed Waterborne Epoxy Semi-Gloss (HP150) Behr Paint Company

Final Assembly: Santa Ana, California, USA

Life Expectancy: Interior / Exterior: 7 / 10 Year(s)

Embodied Carbon: 1.67-2.38 kg CO2eq 

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Aluminum Oxide; Styrene methyl methacrylate copolymer; Fatty acids, soya, epoxidized, Me esters; Nepheline syenite; attapulgite; Polyurethane Resins; Lubricating oils (petroleum), hydrotreated spent; OS 2020; Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate, sodium salt; 1-Propanol, 2-amino-2-methyl-; Amorphous silica; polysiloxane; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Zirconium oxide (ZrO2); Diuron; Ammonium Hydroxide, NOS; Clay; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, methyloxirane and oxirane; Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester; **1,2-Benzisothiazol-3(2H)-one**; Quartz; Siloxanes and Silicones, di-Me, reaction products with silica; **3(2H)-Isothiazolone, 2-methyl-**; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Magnesium oxide (MgO)

Living Building Challenge Criteria: Compliant

I-13 Red List:

☒ LBC Red List Free

% Disclosed: 100% at 100ppm

☐ LBC Red List Approved

VOC Content: <50 g/L

☐ Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

BHR-0006

EXP. 01 APR 2026

Original Issue Date: 2025