



BEHR ULTRA® Exterior Satin Enamel (9850) Behr Paint Company

Final Assembly: Multiple Locations in USA

Life Expectancy: 20 Year(s)

Embodied Carbon: 0.802 kgCO₂eq 

Declared Unit: 1 Square Meter

End of Life Options: Take Back Program (PaintCare), Recyclable (100%)

Ingredients:

Water; 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate; Titanium dioxide; Nepheline syenite; Styrene methyl methacrylate copolymer; Ethanol, 2-butoxy-, benzoate; Aluminum Oxide; Zinc oxide; Polyurethane Resins; attapulgit; 2-Propenoic acid, homopolymer, ammonium salt; Hexanoic acid, 2-ethyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; **Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based**; Amorphous silica; 1-Propanol, 2-amino-2-methyl-, 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; **Benzophenone**; Diuron; Ammonium Hydroxide, NOS; Phosphoric acid, monoethyl ester, potassium salt (1:2); Zirconate(2-), bis[carbonato(2-)-O]dihydroxy-, diammonium, (T-4)-; Zirconium oxide (ZrO₂); **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**; Clay; polysiloxane; Quartz; Carbamic acid, butyl-, 3-iodo-2-propynyl ester; Magnesium oxide (MgO); Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy-; **3(2H)-Isothiazolone, 2-methyl-**; Ammonia

Living Building Challenge Criteria: Compliant

I-13 Red List:

☒ LBC Red List Free

☐ LBC Red List Approved

☐ Declared

% Disclosed: 100% at 100ppm

VOC Content: <50 g/L

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

BHR-0029

EXP. 01 JUL 2026

Original Issue Date: 2025